Measurement and Analysis of Geologically Induced Clutter

John R. Preston
Applied Research Laboratory
P.O. Box 30
State College, PA 16804
phone: (814) 863-1310   fax: (814) 863-8783   email: preston@ciao.arl.psu.edu

LONG-TERM GOALS

The long-term goals of this effort are to:

•   Improve the understanding of the physical mechanisms (below 5kHz) which scatter incident energy multi-statically into a receiver and which can possess target-like characteristics (clutter).

•   Improve the understanding of the effects of seafloor geo-acoustic properties on clutter and reverberation.

•   Improve the understanding of the effects of surface morphology and composition on scattering and clutter.

•   Assess the suitability of current high fidelity reverberation and scattering models for model/data comparison.

OBJECTIVES

The objectives of this effort are to:

•   Design measurements/experiments (including modeling support) to discriminate interface scattering from sub-bottom features and volume inhomogeneities in the ocean bottom in support of geologic clutter reduction (GCR) studies.

•   Design and acquire towed array hardware and acquisition systems to participate in ocean experiments in support of planned GCR experiments.

•   Improve the data processing and handling systems needed to analyze towed array data.

•   Improve suitability of current reverberation models for performance prediction and model/data comparison.

•   Provide a capability and validate schemes for automatically inverting *in situ* array reverberation data for relevant geo-acoustic parameters as well as bottom loss and scattering strength as functions of grazing angle.

Report Documentation Page

1. REPORT DATE **30 SEP 2002**	2. REPORT TYPE	3. DATES COVERED **00-00-2002 to 00-00-2002**
4. TITLE AND SUBTITLE **Measurement and Analysis of Geologically Induced Clutter**		5a. CONTRACT NUMBER
		5b. GRANT NUMBER
		5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)		5d. PROJECT NUMBER
		5e. TASK NUMBER
		5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) **Applied Research Laboratory,,P.O. Box 30,,State College,,PA, 16804**		8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited

13. SUPPLEMENTARY NOTES

14. ABSTRACT

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT **unclassified**	b. ABSTRACT **unclassified**	c. THIS PAGE **unclassified**	**Same as Report (SAR)**	**6**	

APPROACH

The first experiment has been designed and executed in support of the GCR effort at ONR. This was a large experimental effort conducted, after extensive planning near the New Jersey STRATAFORM area in the spring of 2001. This experiment involved researchers from MIT, SACLANTCEN, ARL-PSU and NUWC [1]. ONR's Mace Program Office contributed bistatic source assets. Also, two additional experimental efforts were conducted under the Boundary Characterization Joint Research Program with SACLANTCEN, ARL-PSU, NRL, and DREA of Canada. Those experiments focused on the statistical characterization of ocean boundary interactions but have several objectives in common with the GCR program. Boundary Characterization experiments were conducted in the springs of 2000, 2001 and 2002. Some of this data could be very helpful to the GCR effort since the STRATAFORM was the primary site of the 2001 experiment.

Data was taken over a wide a set of bistatic and monostatic geometries, ranges, frequencies, and pulse parameters to permit broad band analysis and also to test inversion schemes for important geo-acoustic and scattering parameters. Assessing the scattering characteristics of buried features like the meandering river channels identified by Goff, Austin and other ONR researchers [2] is one of the highest priorities.

For the analysis phase, the issue of separating seafloor interface scattering from sub-bottom feature and volume scattering in the bottom is being studied. Recent work noted the importance of fine scale roughness characterization for the Bragg-like scattering component [3]. A study of surface morphology using the high resolution STRATAFORM bathymetry data will be made and compared with fractal (e.g., Goff Jordan) and composite roughness models (e.g. Jackson [4]) to assess merits and shortcomings of these approaches. Refinements to surface roughness models may be implemented where needed. Real 3-D effects for data taken on horizontal line arrays using directional sources have been incorporated into ray based models like GSM. Investigation into how best to incorporate these into higher fidelity codes is ongoing.

The manual inverse scheme used by Preston and Ellis for Rapid Environmental Assessment (REA) [5-7] involved a forward model and match approach using the Generic Sonar Model (GSM) [8] and *apriori* information when possible. That scheme was automated to speed up the bottom parameter estimation process with a simulated annealing (SA) algorithm [11]. This permits near real-time higher quality performance predictions to be made. Minimum least squared error norms have been developed and used to evaluate the results. Using the work of Hamilton [10], the PI has developed a constrained simulated annealing algorithm, which narrows the solution search space. The procedure includes incorporation of propagation loss engines like GSM and ORCA. Recently a multi-frequency optimization capability has been added to the algorithm. The SA inversion methodology has been used on 2000 and 2001 broadband REA reverberation data taken by ARL/Penn State and SACLANTCEN [11,12] as well as some HEP data. The newer scattering strength models developed by Jackson et. al., have also been incorporated into the automated inversion scheme. With the high quality of geo-acoustic ground truth available from the STRATAFORM area, these data sets should be ideal for testing inverse schemes.

WORK COMPLETED

The PI helped plan and then participated in ONR's Geoclutter 2001 experiment (run by MIT's N. Makris) for reverberation in the STRATAFORM off New Jersey in the spring of 2001. Major updates to old pulse processing software were developed to run in near real time for beamformed and matched

filtered output. Geoclutter reverberation data were analyzed at sea and initial results reported at the Geoclutter/Boundary Characterization workshop of Oct 2001 in Halifax [13].

Significant improvements were also made to the REA bottom parameter estimation methodology using the simulated annealing technique described above. The PI also helped plan and then participated in the Boundary Characterization 2001 experiments (run by SACLANTCEN's C. Holland) to measure bottom loss, local scattering, diffuse reverberation, pulse spreading and water-column volume scattering in the STRATAFORM. Using the new REA techniques, reverberation data were analyzed at sea and initial results were reported at the Geoclutter/Boundary Characterization workshop of Oct 2001 in Halifax [12]. Techniques have been significantly improved for post experiment analysis that is ongoing.

The PI has also spent considerable effort in overseeing the building of the new ONR Five Octave Research Array (FORA) at Penn State, under a DURIP award. This new array will be used in the planned 2003 Geoclutter follow-on experiment. The FORA just completed a very successful sea trial, T-Mast 02, (July 02), where a significant amount of data was collected using it as a primary receiver.

RESULTS

Recent results from reverberation analysis on the 2001 experiments and the 2000 Boundary Characterization experiment are reported in [11-13]. As an example, Figure 1 below shows a polar display of stacked monostatic reverberation from the STRATAFORM near site S1, on a towed array in a 50 Hz band centered at 350 Hz. Reverberation is color-coded vs intensity and time is mapped bistatically into location. Fig. 1 also contains the STRATAFORM bathymetry, (in black), sub-bottom horizons (in red) and small surficial features like iceberg scours. Buried river channels, the dendritic structures in black, are also shown (overlay provided by Goff [2]). The arrows indicate the towed array headings. The sources were 0.818 kg SUS charges detonated at 90 m.

IMPACT/APPLICATIONS

A better understanding of sonar clutter is key to improving sonar usability in shallow water. A wide area averaged bottom parameter SA estimation technique for REA such as the one being used here that utilizes directional reverberation measurements could provide a quick way to estimate sonar performance and optimize asset deployment.

TRANSITIONS

These same REA techniques are now being applied to select data from recent HEP experiments as part of ONR 6.2 efforts lead by Dr. R. Wayland in support of the TAMBDA program at NAWC.

RELATED PROJECTS

RECEIVED BEAM POWER in dB vs LOCATION

CRUISE NAME : b2k1

CENTER FREQ. : 350.0

Fig. 1. Polar plot of the stacked (unambiguous) monostatic matched filtered reverberation on STRATAFORM from a SUS in a 50 Hz band centerered at 350 Hz near Site S1. The black arrow directions indicates the 5 array headings, the base of the arrow the array position.

REFERENCES

[1]   Geoclutter Cruise report: Draft copy, MIT, Aug 30,2001

[2]   C. S. Duncan, J. A. Goff , J. A. Austin, C. S. Fulthorpe, "tracking the last sea-level cycle: seafloor morphology and shallow stratigraphy of the latest Quaternary New Jersey middle continental shelf",Marine Geology 170(3-4),pp 395–421 2000.

[3]   J. R. Preston, "Reverberation at the Mid-Atlantic Ridge during the1993 ARSRP experiment seen by R/V Alliance from 200-1400 Hz and some modeling inferences", *J. Acoust. Soc. Am.* 107, 237-259 (2000).

[4]   P. Mourad,, and D. Jackson, "A model/data comparison for low-frequency bottom backcatter," *Journal of the Acoustical Society of America,* **94**, 344-358, 1993.

[5]   D. D. Ellis, J. R. Preston, R. Hollett, and J. Sellschopp, "Analysis of towed array reverberation data from 160 to 4000 Hz during Rapid Response 97," SACLANTCEN SR-280, July 2000.

[6]   J. R. Preston and D. D. Ellis, Summary of Bottom Reverberation Findings and Model/Data Comparisons during Three Rapid Environmental Assessment Trials, Paper 2aUWb3, Conference proceedings for 137[th] ASA meeting in Berlin Germany, March 1999 (Invited paper).

[7]   Ellis, D. D., Preston, J. R., Extracting sea-bottom information from reverberation data, Paper 2aUWb11, Conference proceedings for 137[th] ASA meeting in Berlin Germany, March 1999.

[8]   H. Weinberg, The Generic Sonar Model, Naval Underwater Systems Center, New London, CT, USA, Technical Document 5971D, June 1985.

[9]   J. R. Preston, "Automated bottom parameter extraction from reverberation data with examples from LWAD and HEP data," ARL TM 00-169, 25 October 2000.

[10]   E. L. Hamilton, "Geoacoustic modeling of the seafloor," *J. Acoust. Soc. of Am.*, **68**, 1313-1340, 1980.

[11]   J. R. Preston, "Bottom Parameter Extraction from Long Range Reverberation Measurements," Oceans 2001 Proceedings, Honolulu, Hawaii, November 2001.

[12]   J. R. Preston, "Some shallow water reverberation highlights and bottom parameter extractions in the 325–825 Hz region from the Boundary Characterization experiment," Geoclutter and Boundary Characterization Workshop Proceedings, Halifax, NS, Canada, October 2-3, 2001.

[13]   J. R. Preston, "Some shallow water reverberation and bottom clutter observations near 400 Hz from the 2001 Geoclutter experiment," Geoclutter and Boundary Characterization Workshop Proceedings, Halifax, NS, Canada, October 2-3, 2001.

PUBLICATIONS

J. R. Preston, "Shallow Water Ocean Reverberation Data Analysis and Extraction of Seafloor Geo-acoustic Parameters below 4kHz," Ph.D. Thesis, The Pennsylvania State University, State College, PA, August 2002.

J. R. Preston, "Bottom Parameter Extraction from Long Range Reverberation Measurements," Oceans 2001 Proceedings, Honolulu, Hawaii, November 2001.

J. R. Preston, "Some shallow water reverberation highlights and bottom parameter extractions in the 325–825 Hz region from the Boundary Characterization experiment," Geoclutter and Boundary Characterization Workshop Proceedings, Halifax, NS, Canada, October 2-3, 2001.

J. R. Preston, "Some shallow water reverberation and bottom clutter observations near 400 Hz from the 2001 Geoclutter experiment," Geoclutter and Boundary Characterization Workshop Proceedings, Halifax, NS, Canada, October 2-3, 2001.

J. R. Preston, "Automated bottom parameter extraction from reverberation data with examples from LWAD and HEP data," ARL TM 00-169, 25 October 2000.

Plus parts of many Geoclutter and Boundary Characterization planning documents are towed array design and test inputs.